Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-434-2286

Thread	Direction:
Right-ha	and
Thread	Length:
Betwee	n 3.75 millimeters and 4.25 millimeters
Fastene	er Length:
Betwee	n 9.62 millimeters and 10.38 millimeters
Head S	tyle:
Pan no.	2
Head D	iameter:
Betwee	n 5.5 millimeters and 5.8 millimeters
Head H	eight:
Betwee	n 1.52 millimeters and 1.98 millimeters
First Di	ameter From Head:
2.23 mil	limeters
Distanc	e From Largest Bearing Surface Of Head To End Of First Diameter:
7.0 milli	meters
Interna	I Drive Style:
Cross re	ecess type 1
Thread	Diameter:
3.0 milli	meters
Thread	Pitch In Millimeters:
0.5	
Externa	al Thread Tolerance Class:
6g	
Externa	ally Relieved Body Diameter Quantity:
1	
Color:	
Black	
Materia	l:
Iron allo	by 660
Surface	Preatment:
Oxide	
Surface	Treatment Specification:
Mil-1392	24 cl 4 military specification all treatment responses
Thread	Series Designator:
М	
Shelf Li	ife:
N/a	
Unit Of	Measure:
Demilit	arization:
No	

## NSN 5305-01-434-2286

Externally Relieved Body Screw - Page 2 of 2



Fiig: A003b0

Mil-std (military Standard):

spec.