

View Online at <https://aerobasegroup.com/nsn/5305-01-434-3298>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.531 inches

**Fastener Length:**

Between 1.204 inches and 1.234 inches

**Head Style:**

Flat countersunk undercut

**Head Diameter:**

Between 0.629 inches and 0.634 inches

**Head Height:**

0.490 inches

**Grip Diameter:**

Between 0.3110 inches and 0.3120 inches

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 0.678 inches and 0.698 inches

**Features Provided:**

O ring

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

32.0 microinches threads

**Material:**

Steel comp xm-13

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Mil-c-83488, type 2, class 3 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-83488 spec.