NSN 5305-01-434-3749



Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-434-3749 **Thread Direction:** Right-hand Thread Length: 25.0 millimeters Fastener Length: 25.0 millimeters **Head Style:** Flat chamfer **Head Diameter:** Between 17.6 millimeters and 18.0 millimeters **Head Height:** Between 11.7 millimeters and 12.0 millimeters **Internal Drive Style:** Hexagon **Thread Diameter:** 12.0 millimeters Width Across Flats: Between 12.0 millimeters and 12.1 millimeters Min. Tensile Strength (psi): 1220 megapascals Hardness Rating: 38.0 rockwell c and 44.0 rockwell c Minimum Yield Strength: 1100 megapascals **Thread Pitch In Millimeters:** 1.75 **External Thread Tolerance Class:** 4g6g Material: Steel property class 12.9 **Material Specification:** Din 912 national specification single material response **Surface Treatment:** Zinc and chromate **Surface Treatment Specification:** Astm b633, type 2, class 3 assn standard single treatment response **Thread Series Designator:** Μ Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-434-3749

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0