

View Online at <https://aerobasegroup.com/nsn/5305-01-434-7370>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.156 inches

**Fastener Length:**

Between 0.485 inches and 0.515 inches

**Head Style:**

Knurled no. 5

**Head Diameter:**

Between 0.457 inches and 0.469 inches

**Head Height:**

Between 0.108 inches and 0.112 inches

**First Diameter From Head:**

0.078 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.344 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.112 inches

**Width Across Flats:**

Between 0.250 inches and 0.253 inches

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Steel comp 303

**Material Specification:**

Astm a581, cond a assn standard single material response or astm a582, cond a assn standard single material response

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-c-13924 military specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.