NSN 5305-01-434-7370

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-434-7370 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.156 inches **Fastener Length:** Between 0.485 inches and 0.515 inches **Head Style:** Knurled no. 5 **Head Diameter:** Between 0.457 inches and 0.469 inches **Head Height:** Between 0.108 inches and 0.112 inches **First Diameter From Head:** 0.078 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.344 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.112 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Astm a581, cond a assn standard single material response or astm a582, cond a assn standard single material response **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924 military specification single treatment response **Thread Series Designator:** Unc

_.

Shelf Life:

N/a

NSN 5305-01-434-7370

Externally Relieved Body Screw - Page 2 of 2



Unit Of Measure:	ι	Jnit	Of	Measure:
------------------	---	------	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.