## NSN 5305-01-434-8703

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-434-8703 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.425 inches **Fastener Length:** Between 1.472 inches and 1.502 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.456 inches and 0.508 inches **Grip Diameter:** Between 0.2797 inches and 0.2807 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.2500 inches **Grip Length:** Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Nas4006 assn standard single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas7304 professional/industrial association standard Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-01-434-8703

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0