NSN 5305-01-435-0163

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-435-0163

iew Online at https://aerobasegroup.com/hsr/3505-01-455-0165	
hread Class:	
a	
hread Direction:	
ight-hand	
hread Length:	
184 inches	
astener Length:	
etween 2.8615 inches and 2.8815 inches	
ead Style:	
lat countersunk	
ead Diameter:	
etween 1.643 inches and 1.793 inches	
rip Diameter:	
etween 0.8730 inches and 0.8740 inches	
iternal Drive Style:	
ross recess type 1	
hread Diameter:	
8750 inches	
rip Length:	
etween 1.6775 inches and 1.6975 inches	
hready Qty Per Inch (tpi):	
4	
ountersink Angle:	
etween 99.0 degrees and 101.0 degrees	
laterial:	
teel comp e4340 or steel comp 8740	
laterial Specification:	
lil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 ass	n standard
nd material response	
urface Treatment:	
admium and chromate	
urface Treatment Specification:	
q-p-416, type 2 class 2 federal specification single treatment response	
hread Series Designator:	
njf	
helf Life:	
/a	
nit Of Measure:	
emilitarization:	
0	
iig:	
003b0	

NSN 5305-01-435-0163

Close Tolerance Screw - Page 2 of 2

Mil-std (military Standard):

Mil-s-5000 spec.

