NSN 5305-01-435-0180

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-435-0180

/iew Online at https://aerobasegroup.com/nsn/5305-01-435-0180	
hread Class:	
a	
hread Direction:	
Right-hand	
hread Length:	
.184 inches	
astener Length:	
Between 3.9815 inches and 4.0115 inches	
lead Style:	
lat countersunk	
lead Diameter:	
Between 1.643 inches and 1.793 inches	
Grip Diameter:	
Between 0.9042 inches and 0.9052 inches	
nternal Drive Style:	
Cross recess type 1	
hread Diameter:	
.8750 inches	
Grip Length:	
Between 2.8025 inches and 2.8225 inches	
hready Qty Per Inch (tpi):	
4	
Countersink Angle:	
Between 99.0 degrees and 101.0 degrees	
laterial:	
Steel comp e4340 or steel comp 8740	
laterial Specification:	
/lil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 as	ssn standard
nd material response	
Surface Treatment:	
Cadmium and chromate	
Surface Treatment Specification:	
Qq-p-416, type 2 class 2 federal specification single treatment response	
hread Series Designator:	
Injf	
Shelf Life:	
l/a	
Init Of Measure:	
Demilitarization:	
lo	
iig:	
.003b0	

NSN 5305-01-435-0180

Close Tolerance Screw - Page 2 of 2

Mil-std (military Standard):

Mil-s-5000 spec.

