## NSN 5305-01-435-1090

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-435-1090 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.485 inches and 0.515 inches **Fastener Length:** Between 2.475 inches and 2.525 inches **Head Style:** Hexagon **Head Height:** Between 0.235 inches and 0.265 inches Width Between Flats: Between 0.557 inches and 0.577 inches **First Diameter From Head:** Between 0.170 inches and 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.990 inches and 2.010 inches **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Stainless steel **Material Specification:** Astma581 assn standard single material response or astma582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, ele300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-01-435-1090

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.