Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-435-1090

Thread Class: 3a Thread Direction: Right-hand Thread Length: Between 0.485 inches and 0.515 inches Fastener Length: Between 2.475 inches and 2.525 inches Head Style: Head Style: Between 0.235 inches and 0.265 inches Between 0.235 inches and 0.265 inches Width Between Flats: Between 0.557 inches and 0.577 inches First Diameter From Head: Between 0.577 inches and 0.577 inches Between 0.575 inches and 0.577 inches First Diameter From Head: Between 1.900 inches and 0.2010 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.900 inches and 0.2010 inches Internal Drive Style: Wid internal drive Thread Diameter: 0.250 inches
Thread Direction:Right-handThread Length:Between 0.485 inches and 0.515 inchesFastener Length:Between 2.475 inches and 2.525 inchesHead Style:HexagonHead Height:Between 0.235 inches and 0.265 inchesWith Between Flats:Between 0.557 inches and 0.577 inchesFirst Diameter From Head:Between 0.170 inches and 0.180 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:Between 1.990 inches and 2.010 inchesInternal Drive Style:Wo internal driveStore I.Distance From Largest Bearing Surface Of Head To End Of First Diameter:Between 1.990 inches and 2.010 inchesInternal Drive Style:Wo internal driveStore I.Store I.Between I.Store I.Between I.Store I.Between I.
Right-handThread Length:Between 0.485 inches and 0.515 inchesFastener Length:Between 2.475 inches and 2.525 inchesHead Style:Head Style:HexagonHead Height:Between 0.235 inches and 0.265 inchesWidth Between Flats:Between 0.557 inches and 0.577 inchesFirst Diameter From Head:Between 0.170 inches and 0.577 inchesBetween 0.170 inches and 0.180 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:Between 1.990 inches and 2.010 inchesInternal Drive Style:W/o internal driveThread Diameter:0.250 inches0.250 inchesBetween 0.250 inchesBetween 0.250 inches and 0.180 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:Between 1.990 inches and 2.010 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:Between 1.990 inches and 2.010 inchesBetween 1.990 inches and 2.010 inchesHerral Drive Style:Wo internal driveThread Diameter:0.250 inchesBetween Diameter:0.250 inchesBetween Diameter:Between
Thread Length: Between 0.485 inches and 0.515 inches Fastener Length: Between 2.475 inches and 2.525 inches Head Style: Head Style: Hexagon Head Height: Between 0.235 inches and 0.265 inches Width Between Flats: Between 0.557 inches and 0.577 inches First Diameter From Head: Between 0.170 inches and 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.990 inches and 2.010 inches Internal Drive Style: W/o internal drive Thread Diameter: 0.250 inches
Between 0.485 inches and 0.515 inches Fastener Length: Between 2.475 inches and 2.525 inches Head Style: Head Style: Hexagon Head Height: Between 0.235 inches and 0.265 inches Width Between Flats: Between 0.577 inches and 0.577 inches First Diameter From Head: Between 0.170 inches and 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.990 inches and 2.010 inches Internal Drive Style: W/o internal drive Thread Diameter: 0.250 inches
Fastener Length: Between 2.475 inches and 2.525 inches Head Style: Hexagon Head Height: Between 0.235 inches and 0.265 inches Width Between Flats: Between 0.557 inches and 0.577 inches First Diameter From Head: Between 0.170 inches and 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.990 inches and 2.010 inches Internal Drive Style: W/o internal drive Thread Diameter: 0.250 inches
Between 2.475 inches and 2.525 inches Head Style: Hexagon Head Height: Between 0.235 inches and 0.265 inches Vidth Between Flats: Between 0.557 inches and 0.577 inches First Diameter From Head: Between 0.170 inches and 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.990 inches and 2.010 inches Internal Drive Style: Vio internal drive Thread Diameter: 0.250 inches
Head Style:HexagonHead Height:Between 0.235 inches and 0.265 inchesWidth Between Flats:Between 0.557 inches and 0.577 inchesFirst Diameter From Head:Between 0.170 inches and 0.180 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:Between 1.990 inches and 2.010 inchesInternal Drive Style:W/o internal driveDistance From Largest Bearing Surface Of Head To End Of First Diameter:Distance Trom Largest Bearing Surface Of Head To End Of First Diameter:Distance Internal Drive Style:Wo internal driveThread Diameter:0.250 inchesDistance Internal ComplexityDistance Style:Distance Style:<
Hexagon Head Height: Between 0.235 inches and 0.265 inches Width Between Flats: Between 0.557 inches and 0.577 inches First Diameter From Head: Between 0.170 inches and 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.990 inches and 2.010 inches Hernal Drive Style: W/o internal drive Thread Diameter: 0.250 inches
Head Height: Between 0.235 inches and 0.265 inches Width Between Flats: Between 0.557 inches and 0.577 inches First Diameter From Head: Between 0.170 inches and 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.990 inches and 2.010 inches Herenal Drive Style: W/o internal drive Thread Diameter: 0.250 inches
Between 0.235 inches and 0.265 inches Width Between Flats: Between 0.557 inches and 0.577 inches First Diameter From Head: Between 0.170 inches and 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.990 inches and 2.010 inches Internal Drive Style: W/o internal drive Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi):
Width Between Flats:Between 0.557 inches and 0.577 inchesFirst Diameter From Head:Between 0.170 inches and 0.180 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:Between 1.990 inches and 2.010 inchesInternal Drive Style:W/o internal driveThread Diameter:0.250 inchesThready Qty Per Inch (tpi):
Between 0.557 inches and 0.577 inches First Diameter From Head: Between 0.170 inches and 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.990 inches and 2.010 inches Internal Drive Style: W/o internal drive Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi):
First Diameter From Head: Between 0.170 inches and 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.990 inches and 2.010 inches Internal Drive Style: W/o internal drive Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi):
Between 0.170 inches and 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.990 inches and 2.010 inches Internal Drive Style: W/o internal drive Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi):
Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.990 inches and 2.010 inches Internal Drive Style: W/o internal drive Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi):
Between 1.990 inches and 2.010 inches Internal Drive Style: W/o internal drive Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi):
Internal Drive Style: W/o internal drive Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi):
W/o internal drive Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi):
Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi):
0.250 inches Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi):
20
Externally Relieved Body Diameter Quantity:
1
Material:
Stainless steel
Material Specification:
Astma581 assn standard single material response or astma582 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-f-14072, ele300 military specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5305-01-435-1090

Externally Relieved Body Screw - Page 2 of 2



Fiig: A003b0

Mil-std (military Standard):

Mil-f-14072 spec.