## NSN 5305-01-435-1745

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-435-1745

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.650 inches and 0.750 inches
Fastener Length:
0.750 inches
Head Style:
Pan
Head Diameter:
Between 0.473 inches and 0.492 inches
Head Height:
Between 0.162 inches and 0.175 inches
Internal Drive Style:
Cross recess type 1
End Application:
Mrap buffalo mk2a2; mrap - cougar; mrap - m-atv dv178; mrap - cougar cat1 a2
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
20
20 Min. Tensile Strength (psi):
Min. Tensile Strength (psi):
Min. Tensile Strength (psi): 80000 pounds per square inch
Min. Tensile Strength (psi): 80000 pounds per square inch Screw Material:
Min. Tensile Strength (psi): 80000 pounds per square inch Screw Material: Stainless steel
Min. Tensile Strength (psi): 80000 pounds per square inch Screw Material: Stainless steel Screw Material Specification:
Min. Tensile Strength (psi): 80000 pounds per square inch Screw Material: Stainless steel Screw Material Specification: Cres comp 316 only federal specification single material response
Min. Tensile Strength (psi): 80000 pounds per square inch Screw Material: Stainless steel Screw Material Specification: Cres comp 316 only federal specification single material response Screw Surface Treatment:
Min. Tensile Strength (psi): 80000 pounds per square inch Screw Material: Stainless steel Screw Material Specification: Cres comp 316 only federal specification single material response Screw Surface Treatment: Passivate
Min. Tensile Strength (psi): 80000 pounds per square inch Screw Material: Stainless steel Screw Material Specification: Cres comp 316 only federal specification single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification:
Min. Tensile Strength (psi):  80000 pounds per square inch  Screw Material:  Stainless steel  Screw Material Specification:  Cres comp 316 only federal specification single material response  Screw Surface Treatment:  Passivate  Screw Surface Treatment Specification:  Qq-p-35 federal specification single treatment response
Min. Tensile Strength (psi):  80000 pounds per square inch  Screw Material:  Stainless steel  Screw Material Specification:  Cres comp 316 only federal specification single material response  Screw Surface Treatment:  Passivate  Screw Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Special Features:
Min. Tensile Strength (psi):  80000 pounds per square inch  Screw Material: Stainless steel  Screw Material Specification: Cres comp 316 only federal specification single material response  Screw Surface Treatment: Passivate  Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response  Special Features: Cres comp 316 only
Min. Tensile Strength (psi): 80000 pounds per square inch Screw Material: Stainless steel Screw Material Specification: Cres comp 316 only federal specification single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Special Features: Cres comp 316 only Thread Series Designator:
Min. Tensile Strength (psi): 80000 pounds per square inch Screw Material: Stainless steel Screw Material Specification: Cres comp 316 only federal specification single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Special Features: Cres comp 316 only Thread Series Designator: Unc
Min. Tensile Strength (psi): 80000 pounds per square inch Screw Material: Stainless steel Screw Material Specification: Cres comp 316 only federal specification single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Special Features: Cres comp 316 only Thread Series Designator: Unc Departure From Cited Document:
Min. Tensile Strength (psi): 80000 pounds per square inch Screw Material: Stainless steel Screw Material Specification: Cres comp 316 only federal specification single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Special Features: Cres comp 316 only Thread Series Designator: Unc Departure From Cited Document: As modified by material

--

## NSN 5305-01-435-1745

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0