## NSN 5305-01-435-3294

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-435-3294

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
0.694 inches	
Fastener Length:	
Between 1.3665 inches and 1.3965 inches	
Head Style:	
Flat countersunk	
Head Diameter:	
Between 0.809 inches and 0.892 inches	
Grip Diameter:	
Between 0.4360 inches and 0.4370 inches	
nternal Drive Style:	
Cross recess type 1	
Thread Diameter:	
0.4375 inches	
Grip Length:	
Between 0.6775 inches and 0.6973 inches	
Гhready Qty Per Inch (tpi):	
20	
Countersink Angle:	
Between 99.0 degrees and 101.0 degrees	
Material:	
Steel comp e4340 or steel comp 8740	
Material Specification:	
Vil-s-5000 military specification 1st material response	or mil-s-6049 military specification 2nd material response or ams 6322 assn standard
2nd material response	
Surface Treatment:	
Cadmium and chromate	
Surface Treatment Specification:	
Qq-p-416, type 2 class 2 federal specification single to	reatment response
Thread Series Designator:	
Unjf	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A003b0	

NSN 5305-01-435-3294

Close Tolerance Screw - Page 2 of 2

Mil-std (military Standard):

Mil-s-5000 spec.

