## NSN 5305-01-435-3316



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-435-3316 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.694 inches **Fastener Length:** Between 1.554 inches and 1.584 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.809 inches and 0.892 inches **Grip Diameter:** Between 0.4360 inches and 0.4370 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.4375 inches **Grip Length:** Between 0.8650 inches and 0.8850 inches Thready Qty Per Inch (tpi): 20 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp e4340 and steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No Fiig:

A003b0

**Demilitarization:** 

## NSN 5305-01-435-3316

Close Tolerance Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.