## NSN 5305-01-435-3462

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-435-3462

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
0.694 inches	
Fastener Length:	
Between 2.2415 inches and	2.2715 inches
Head Style:	
Flat countersunk	
Head Diameter:	
Between 0.809 inches and (	.892 inches
Grip Diameter:	
Between 0.4360 inches and	0.4370 inches
nternal Drive Style:	
Cross recess type 1	
Thread Diameter:	
0.4375 inches	
Grip Length:	
Between 1.5525 inches and	1.5725 inches
Thready Qty Per Inch (tpi)	
20	
Countersink Angle:	
Between 99.0 degrees and	101.0 degrees
Material:	
Steel comp e4340 or steel	comp 8740
Material Specification:	
√il-s-5000 military specifica	tion 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard
2nd material response	
Surface Treatment:	
Cadmium and chromate	
Surface Treatment Specifi	cation:
Qq-p-416, type 2 class 2 fe	deral specification single treatment response
Thread Series Designator	
Unjf	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A003b0	

## NSN 5305-01-435-3462

Close Tolerance Screw - Page 2 of 2

## Mil-std (military Standard):

Mil-s-5000 spec.

