## NSN 5305-01-435-5755



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-435-5755 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.735 inches **Fastener Length:** Between 2.470 inches and 2.500 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.927 inches and 1.019 inches **Grip Diameter:** Between 0.4985 inches and 0.4995 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.5000 inches **Grip Length:** Between 1.7400 inches and 1.7600 inches Thready Qty Per Inch (tpi): 20 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:
-Demilitarization:
No
Fiig:
A003b0

## NSN 5305-01-435-5755

Close Tolerance Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.