

View Online at <https://aerobasegroup.com/nsn/5305-01-435-5829>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.735 inches

**Fastener Length:**

Between 4.0950 inches and 4.1250 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.927 inches and 1.019 inches

**Grip Diameter:**

Between 0.4985 inches and 0.4995 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.5000 inches

**Grip Length:**

Between 3.3650 inches and 3.3850 inches

**Thready Qty Per Inch (tpi):**

20

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp e4340 or steel comp 8740

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard 2nd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2 class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.