## NSN 5305-01-435-6493

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-435-6493

new Online at https://aerobasegroup.com/nsn/5305-01-435-6493	
hread Class:	
a	
Thread Direction:	
Right-hand	
hread Length:	
.840 inches	
astener Length:	
Between 2.3875 inches and 2.4175 inches	
lead Style:	
ilat countersunk	
lead Diameter:	
Between 1.047 inches and 1.146 inches	
Grip Diameter:	
Between 0.5605 inches and 0.5615 inches	
nternal Drive Style:	
Cross recess type 1	
hread Diameter:	
.5625 inches	
Grip Length:	
Between 1.5525 inches and 1.5725 inches	
hready Qty Per Inch (tpi):	
8	
Countersink Angle:	
Setween 99.0 degrees and 101.0 degrees	
faterial:	
Steel comp e4340 or steel comp 8740	
Naterial Specification:	
/il-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn stand	lard
Ind material response	
Surface Treatment:	
Cadmium and chromate	
Surface Treatment Specification:	
Qq-p-416, type 2 class 2 federal specification single treatment response	
hread Series Designator:	
Jnjf	
Shelf Life:	
I/a	
Init Of Measure:	
Demilitarization:	
lo	
iig:	

## NSN 5305-01-435-6493

Close Tolerance Screw - Page 2 of 2

## Mil-std (military Standard):

Mil-s-5000 spec.

