## NSN 5305-01-435-7885

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-435-7885

View Online at https://aerobasegroup.com/nsn/5305-01-435-7885	
Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
0.840 inches	
Fastener Length:	
Between 2.6375 inches and 2.6675 inches	
Head Style:	
Flat countersunk	
Head Diameter:	
Between 1.047 inches and 1.146 inches	
Grip Diameter:	
Between 0.5605 inches and 0.5615 inches	
Internal Drive Style:	
Cross recess type 1	
Thread Diameter:	
0.5625 inches	
Grip Length:	
Between 1.8025 inches and 1.8225 inches	
Thready Qty Per Inch (tpi):	
18	
Countersink Angle:	
Between 99.0 degrees and 101.0 degrees	
Material:	
Steel comp e4340 or steel comp 8740	
Material Specification:	
Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response	e or ams6322 assn standard
2nd material response	
Surface Treatment:	
Cadmium and chromate	
Surface Treatment Specification:	
Qq-p-416, type 2 class 2 federal specification single treatment response	
Thread Series Designator:	
Unjf	
Shelf Life:	
N/a	
Unit Of Measure:	
 Demilitarization:	
Filg:	
A003b0	

## NSN 5305-01-435-7885

Close Tolerance Screw - Page 2 of 2

## Mil-std (military Standard):

Mil-s-5000 spec.

