NSN 5305-01-435-8304

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-435-8304 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.578 inches **Fastener Length:** Between 4.438 inches and 4.468 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.691 inches and 0.765 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Internal Drive Style:** Cross recess type iii **Thread Diameter:** 0.375 inches **Grip Length:** Between 3.865 inches and 3.885 inches Thready Qty Per Inch (tpi): 24

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Surface Finish:

32.0 microinches threads

Material:

Steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5305-01-435-8304

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.