

View Online at <https://aerobasegroup.com/nsn/5305-01-435-8519>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.840 inches

Fastener Length:

Between 3.6375 inches and 3.6675 inches

Head Style:

Flat countersunk

Head Diameter:

Between 1.047 inches and 1.146 inches

Grip Diameter:

Between 0.5605 inches and 0.5615 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.5625 inches

Grip Length:

Between 2.8025 inches and 2.8225 inches

Thready Qty Per Inch (tpi):

18

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2 class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.