NSN 5305-01-435-8691

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-435-8691

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
0.840 inches	
Fastener Length:	
Between 4.325 inches and 4.	355 inches
Head Style:	
Flat countersunk	
Head Diameter:	
Between 1.047 inches and 1.	146 inches
Grip Diameter:	
Between 0.5605 inches and 0	.5615 inches
Internal Drive Style:	
Cross recess type 1	
Thread Diameter:	
).5625 inches	
Grip Length:	
Between 3.4900 inches and 3	.5100 inches
Thready Qty Per Inch (tpi):	
18	
Countersink Angle:	
Between 99.0 degrees and 10	01.0 degrees
Material:	
Steel comp e4340 or steel co	mp 8740
Material Specification:	
Vil-s-5000 military specification	on 1st material response or mil-s-6049 military specification 2nd material response or asm 6322 assn standard
2nd material response	
Surface Treatment:	
Cadmium and chromate	
Surface Treatment Specific	ation:
Qq-p-416, type 2 class 2 fed	eral specification single treatment response
Thread Series Designator:	
Unjf	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A003b0	

NSN 5305-01-435-8691

Close Tolerance Screw - Page 2 of 2

Mil-std (military Standard):

Mil-s-5000 spec.

