

View Online at <https://aerobasegroup.com/nsn/5305-01-435-9807>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.469 inches

Fastener Length:

Between 1.1415 inches and 1.1715 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.574 inches and 0.637 inches

Locking Feature:

Patch threads

Grip Diameter:

Between 0.3266 inches and 0.3276 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.3125 inches

Grip Length:

Between 0.6775 inches and 0.6975 inches

Thready Qty Per Inch (tpi):

24

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp e4340 fastener or steel comp 8740 fastener

Material Specification:

Mil-s-5000 military specification 1st material response fastener or mil-s-6049 military specification 2nd material response fastener or ams 6322 assn standard 2nd material response fastener

Surface Treatment:

Cadmium fastener and chromate fastener

Surface Treatment Specification:

Qq-p-416, type 2 class 2 federal specification single treatment response fastener

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.