## NSN 5305-01-436-0614

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-436-0614

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 0.469 inches   |
| Fastener Length:   |
| Between 1.766 inches and 1.796 inches  |
| Head Style:  |
| Flat countersunk   |
| Head Diameter:   |
| Between 0.575 inches and 0.635 inches  |
| Grip Diameter:   |
| Between 0.3110 inches and 0.3120 inches  |
| Internal Drive Style:  |
| Cross recess type 1  |
| Thread Diameter:   |
| 0.3125 inches  |
| Grip Length:   |
| Between 1.302 inches and 1.322 inches  |
| Thready Qty Per Inch (tpi):  |
| 24   |
| Min. Tensile Strength (psi):   |
| 160000 pounds per square inch  |
| Countersink Angle:   |
| Between 99.0 degrees and 101.0 degrees   |
| Material:  |
| Titanium alloy uns r56400  |
| Material Specification:  |
| Ams 4928 assn standard single material response or ams 4967 assn standard single material response |
| Surface Treatment:   |
| Aluminum   |
| Surface Treatment Specification:   |
| Nas4006 assn standard single treatment response  |
| Thread Series Designator:  |
| Unjf   |
| Specification Data:  |
| 80205-nas7305 professional/industrial association standard   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

## NSN 5305-01-436-0614

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

