NSN 5305-01-436-1291

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-436-1291 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.694 inches **Fastener Length:** Between 2.804 inches and 2.834 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.810 inches and 0.889 inches **Grip Diameter:** Between 0.4360 inches and 0.4370 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.4375 inches **Grip Length:** Between 2.115 inches and 2.135 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Nas4006 assn standard single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas7307 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-436-1291

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0