NSN 5305-01-436-1734

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-436-1734 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.425 inches **Fastener Length:** Between 1.160 inches and 1.190 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.456 inches and 0.508 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.740 inches and 0.760 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 4340 and steel comp 8740 **Material Specification:** Mil-s-6049 military specification 1st material response or ams6322 assn standard 2nd material response **Surface Treatment:** Cadmium and chromate **Thread Series Designator:** Unjf **Specification Data:** 80205-nas7104 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

A003b0

NSN 5305-01-436-1734

Close Tolerance Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6049 spec.