## NSN 5305-01-436-2826

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-436-2826

| Thread Class   |
|--|
| Thread Class:  |
| 3a   |
| Thread Direction:  |
| Right-hand Thread Longth   |
| Thread Length:   |
| 0.840 inches   |
| Fastener Length:   |
| Between 2.637 inches and 2.667 inches  |
| Head Style:  |
| Flat countersunk   |
| Head Diameter:   |
| Between 1.047 inches and 1.144 inches  |
| Grip Diameter:   |
| Between 0.5605 inches and 0.5615 inches  |
| Internal Drive Style:  |
| Cross recess type 1  |
| Thread Diameter:   |
| 0.5625 inches  |
| Grip Length:   |
| Between 1.802 inches and 1.822 inches  |
| Thready Qty Per Inch (tpi):  |
| 18   |
| Min. Tensile Strength (psi):   |
| 160000 pounds per square inch  |
| Countersink Angle:   |
| Between 99.0 degrees and 101.0 degrees   |
| Material:  |
| Titanium alloy uns r56400  |
| Material Specification:  |
| Ams 4928 assn standard single material response or ams 4967 assn standard single material response |
| Surface Treatment:   |
| Aluminum Suurface Trackment Specification  |
| Surface Treatment Specification:   |
| Nas4006 assn standard single treatment response  Thread Series Designators                         |
| Thread Series Designator:  |
| Unif Specification Date:   |
| Specification Data:  |
| 80205-nas7309 professional/industrial association standard  Shelf Life:                            |
| N/a  |
|  |
| Unit Of Measure:   |

-

## NSN 5305-01-436-2826

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0