Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-436-5486

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.266 inches
Fastener Length:
Between 0.344 inches and 0.375 inches
Head Style:
Flat countersunk
Head Diameter:
0.305 inches
Washer Quantity:
1 Internal Drive Stude:
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.164 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
125000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Primary Washer Outside Diameter:
Between 0.640 inches and 0.660 inches
Primary Washer Style:
Finishing
Primary Washer Material Thickness:
Between 0.015 inches and 0.021 inches
Material:
Steel comp 1050 primary washer
Material Specification:
Sae 1050 assn standard single material response primary washer
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 ty2 cl3 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a

NSN 5305-01-436-5486

Assembled Washer Screw - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0