## NSN 5305-01-436-7178

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-436-7178

Thread Class:
Thread Direction:
Right-hand Thread Longth
Thread Length: 0.528 inches
Fastener Length:  Between 1.325 inches and 1.355 inches
Head Style: Flat countersunk
Head Diameter:
Between 0.928 inches and 1.016 inches
Grip Diameter:  Between 0.5297 inches and 0.5307 inches
Internal Drive Style:
Cross recess type 1  Thread Diameter:
0.5000 inches
Grip Length:  Between 0.802 inches and 0.822 inches
Thready Qty Per Inch (tpi):
20 Min Tanaila Strangth (nai):
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees  Material:
Titanium alloy uns r56400
Material Specification:  Ama 4029 acceptandard single material response, or ama 4067 acceptandard single material response.
Ams 4928 assn standard single material response or ams 4967 assn standard single material response  Surface Treatment:
Aluminum
Surface Treatment Specification:
Nas4006 assn standard single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas7608 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
one of modouro.

--

## NSN 5305-01-436-7178

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0