

View Online at <https://aerobasegroup.com/nsn/5305-01-436-7234>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.953 inches

Fastener Length:

Between 2.251 inches and 2.281 inches

Head Style:

Flat countersunk

Head Diameter:

Between 1.201 inches and 1.272 inches

Grip Diameter:

Between 0.6226 inches and 0.6232 inches

Internal Drive Style:

High-torque

Thread Diameter:

0.625 inches

Grip Length:

Between 1.303 inches and 1.323 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4140 or steel comp 4340 or steel comp 8735 or steel comp 8740 or steel comp 6150

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response or mil-s-8503 military specification 5th material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses

Thread Series Designator:

Unjf

Specification Data:

80205-nas590 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.