NSN 5305-01-436-9724

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-436-9724

Thread Class: 3a Thread Direction: Right-hand Thread Length: 0.761 inches Fastener Length: 2.136 inches Head Style: Flat countersunk Head Diameter: Between 0.951 inches and 1.013 inches Head Height: 0.222 inches Grip Diameter: Between 0.498 inches and 0.499 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.500 inches Grip Length: 1.375 inches Thready Qty Per Inch (tpi): 20 Countersink Angle: 100.0 degrees
Thread Direction: Right-hand Thread Length: 0.761 inches Fastener Length: 2.136 inches Head Style: Flat countersunk Head Diameter: Between 0.951 inches and 1.013 inches Head Height: 0.222 inches Grip Diameter: Between 0.498 inches and 0.499 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.500 inches Grip Length: 1.375 inches Thready Qty Per Inch (tpi): 20
Right-handRight-handThread Length:0.761 inchesFastener Length:2.136 inchesHead Style:Flat countersunkHead Diameter:Between 0.951 inches and 1.013 inchesHead Height:0.222 inchesGrip Diameter:Between 0.498 inches and 0.499 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.500 inchesGrip Length:1.375 inchesThready Qty Per Inch (tpi):20Countersink Angle:
Thread Length: 0.761 inches Fastener Length: 2.136 inches Head Style: Flat countersunk Head Diameter: Between 0.951 inches and 1.013 inches Head Height: 0.222 inches Grip Diameter: Between 0.498 inches and 0.499 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.500 inches Grip Length: 1.375 inches Thready Qty Per Inch (tpi): 20
0.761 inches Fastener Length: 2.136 inches Head Style: Flat countersunk Head Diameter: Between 0.951 inches and 1.013 inches Head Height: 0.222 inches Grip Diameter: Between 0.498 inches and 0.499 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.500 inches Grip Length: 1.375 inches Thready Qty Per Inch (tpi): 20
Fastener Length:2.136 inchesHead Style:Flat countersunkHead Diameter:Between 0.951 inches and 1.013 inchesHead Height:0.222 inchesGrip Diameter:Between 0.498 inches and 0.499 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.500 inchesGrip Length:1.375 inchesThready Qty Per Inch (tpi):20Countersink Angle:
2.136 inches Head Style: Flat countersunk Head Diameter: Between 0.951 inches and 1.013 inches Head Height: 0.222 inches Grip Diameter: Between 0.498 inches and 0.499 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.500 inches Grip Length: 1.375 inches Thready Qty Per Inch (tpi): 20 Countersink Angle:
Head Style:Flat countersunkHead Diameter:Between 0.951 inches and 1.013 inchesHead Height:0.222 inchesGrip Diameter:Between 0.498 inches and 0.499 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.500 inchesGrip Length:1.375 inchesThready Qty Per Inch (tpi):20Countersink Angle:
Flat countersunk Head Diameter: Between 0.951 inches and 1.013 inches Head Height: 0.222 inches Grip Diameter: Between 0.498 inches and 0.499 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.500 inches Grip Length: 1.375 inches Thready Qty Per Inch (tpi): 20 Countersink Angle:
Head Diameter: Between 0.951 inches and 1.013 inches Head Height: 0.222 inches Grip Diameter: Between 0.498 inches and 0.499 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.500 inches Grip Length: 1.375 inches Thready Qty Per Inch (tpi): 20 Countersink Angle:
Between 0.951 inches and 1.013 inches Head Height: 0.222 inches Grip Diameter: Between 0.498 inches and 0.499 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.500 inches Grip Length: 1.375 inches Thready Qty Per Inch (tpi): 20 Countersink Angle:
Head Height:0.222 inchesGrip Diameter:Between 0.498 inches and 0.499 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.500 inchesGrip Length:1.375 inchesThready Qty Per Inch (tpi):20Countersink Angle:
0.222 inches Grip Diameter: Between 0.498 inches and 0.499 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.500 inches Grip Length: 1.375 inches Thready Qty Per Inch (tpi): 20 Countersink Angle:
Grip Diameter: Between 0.498 inches and 0.499 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.500 inches Grip Length: 1.375 inches Thready Qty Per Inch (tpi): 20 Countersink Angle:
Between 0.498 inches and 0.499 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.500 inches Grip Length: 1.375 inches Thready Qty Per Inch (tpi): 20 Countersink Angle:
Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.500 inches Grip Length: 1.375 inches Thready Qty Per Inch (tpi): 20 Countersink Angle:
Offset cruciform (torque set) Thread Diameter: 0.500 inches Grip Length: 1.375 inches Thready Qty Per Inch (tpi): 20 Countersink Angle:
Thread Diameter: 0.500 inches Grip Length: 1.375 inches Thready Qty Per Inch (tpi): 20 Countersink Angle:
0.500 inches Grip Length: 1.375 inches Thready Qty Per Inch (tpi): 20 Countersink Angle:
Grip Length: 1.375 inches Thready Qty Per Inch (tpi): 20 Countersink Angle:
1.375 inches Thready Qty Per Inch (tpi): 20 Countersink Angle:
Thready Qty Per Inch (tpi): 20 Countersink Angle:
20 Countersink Angle:
Countersink Angle:
100.0 degrees
Product Name:
Navy special project
Material:
Steel comp h11
Material Specification:
Ams6487 assn standard single material response
Surface Treatment Specification:
Nas4006 sermatal assn standard single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5305-01-436-9724

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

