## NSN 5305-01-437-0007

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-437-0007 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.403 inches **Fastener Length:** Between 1.450 inches and 1.480 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.464 inches and 0.506 inches **Shoulder Diameter:** 0.279 inches all shoulders and 0.280 inches all shoulders **Shoulder Length:** 1.052 inches all shoulders and 1.072 inches all shoulders **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round all shoulders Material: Steel comp 4140 or steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 ty2 cl2 federal specification single treatment response **Thread Series Designator:** Unjf

--

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5305-01-437-0007

Shoulder Screw - Page 2 of 2



em			

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.