NSN 5305-01-437-1258

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-437-1258

Thread Cl	ass:
3a	
Thread Di	rection:
Right-hand	I Contraction of the second
Thread Le	ngth:
0.578 inch	es
Fastener I	_ength:
Between 1	.501 inches and 1.531 inches
Head Style	e :
Flat counte	ersunk
Head Diar	neter:
Between 0	.704 inches and 0.762 inches
Grip Diam	eter:
Between 0	.3731 inches and 0.3737 inches
Internal D	rive Style:
High-torqu	e
Thread Di	ameter:
0.375 inch	es
Grip Leng	th:
Between 0	.928 inches and 0.948 inches
Thready C	ty Per Inch (tpi):
24	
Min. Tens	ile Strength (psi):
160000 po	unds per square inch
Countersi	nk Angle:
Between 9	9.0 degrees and 101.0 degrees
Surface F	nish:
32.0 micro	inches threads
Material:	
Plastic poly	vamide locking feature
Material S	pecification:
Ams 4928	assn standard single material response fastener or ams 4967 assn standard single material response fastener
Surface T	reatment:
Passivate	fastener
Surface T	reatment Specification:
Qq-p-35 fe	deral specification single treatment response fastener
Thread Se	ries Designator:
Unjf	
Specificat	ion Data:
80205-nas	1166 professional/industrial association standard
Shelf Life	
N/a	

NSN 5305-01-437-1258

Close Tolerance Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

