NSN 5305-01-437-4588

Setscrew - Page 1 of 2

3a





Thread Class: Thread Direction: Right-hand Thread Length: Between 1.470 inches and 1.530 inches Fastener Length: Between 6.615 inches and 6.635 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.921 inches and 0.938 inches **Head Height:** Between 0.616 inches and 0.625 inches **Point Length:** 5.125 inches **Point Diameter:** Between 0.4986 inches and 0.4991 inches **Point Style:** Dog **Internal Drive Style:** Hexagon **Thread Diameter:** 0.625 inches Width Across Flats: Between 0.500 inches and 0.505 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Point Chamfer Angle:** Between 40.0 degrees and 50.0 degrees Material: Steel uns k03104 **Material Specification:** Astm a574 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification all treatment responses **Thread Series Designator:**

Unc

11

NSN 5305-01-437-4588

Setscrew - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

