

View Online at <https://aerobasegroup.com/nsn/5305-01-437-5059>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.763 inches

Fastener Length:

Between 0.782 inches and 0.813 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.213 inches and 0.225 inches

Internal Drive Style:

Cross recess type iii

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

125000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Screw Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740

Screw Material Specification:

Mil-s-6758 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Screw Surface Treatment:

Cadmium

Screw Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Thread Series Designator:

Unjc

Specification Data:

80205-nas514 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6758 spec.