NSN 5305-01-437-7062

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-437-7062

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.256 inches
Fastener Length:
Between 0.281 inches and 0.312 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.177 inches and 0.225 inches
Internal Drive Style:
Torque set
Thread Diameter:
0.112 inches
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Screw Material:
Iron alloy 660
Locking Feature Material:
Plastic polychlorotrifluoroethylene
Screw Material Specification:
Ams 5737 assn standard single material response
Locking Feature Material Specification:
Ams 3650 assn standard single material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Bearing Surface Of Head Surface Finish:
32.0 microinches
Thread Surface Finish:
32.0 microinches
Thread Series Designator:
Unjc
Specification Data:
80205-nas1189 professional/industrial association standard

NSN 5305-01-437-7062

Machine Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0