NSN 5305-01-437-7293

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-437-7293 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.338 inches **Fastener Length:** Between 0.407 inches and 0.438 inches **Head Style:** Fillister **Head Diameter:** Between 0.178 inches and 0.183 inches **Head Height:** Between 0.059 inches and 0.069 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Iron alloy 660 **Locking Feature Material:** Plastic polychlorotrifluoroethylene **Screw Material Specification:** Ams 5737 assn standard single material response **Locking Feature Material Specification:** Ams 3650 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Bearing Surface Of Head Surface Finish:** 32.0 microinches **Shank Surface Finish:** 32.0 microinches **Thread Surface Finish:** 32.0 microinches **Thread Series Designator:**

Unjc

NSN 5305-01-437-7293

Machine Screw - Page 2 of 2



Spec	ifi	cation	Data
------	-----	--------	------

80205-nas1191 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0