NSN 5305-01-438-0371

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-438-0371

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.276 inches |
| Fastener Length: |
| 1.651 inches |
| Head Style: |
| Flat fillister |
| Head Diameter: |
| Between 0.306 inches and 0.313 inches |
| Head Height: |
| Between 0.103 inches and 0.118 inches |
| Grip Diameter: |
| Between 0.1885 inches and 0.1895 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| 1.375 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Product Name: |
| Navy special project |
| Material: |
| Stainless steel |
| Material Specification: |
| Ams5737 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas1123 professional/industrial association standard |
| Shelf Life: |

N/a

NSN 5305-01-438-0371

Close Tolerance Screw - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A003b0