## NSN 5305-01-438-2245

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-438-2245 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.276 inches **Fastener Length:** Between 1.449 inches and 1.479 inches **Head Style:** Flat fillister **Head Diameter:** Between 0.306 inches and 0.313 inches **Head Height:** Between 0.103 inches and 0.118 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** Between 1.178 inches and 1.198 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches threads **Product Name:** Navy special project Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** 

Unjc

**Specification Data:** 

80205-nas1123 professional/industrial association standard

## NSN 5305-01-438-2245

Close Tolerance Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0