NSN 5305-01-438-2250

Thread Class:

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-438-2250

3a
Thread Direction:
Right-hand
Thread Length:
0.276 inches
Fastener Length:
Between 1.823 inches and 1.853 inches
Head Style:
Flat fillister
Head Diameter:
Between 0.306 inches and 0.313 inches
Head Height:
Between 0.103 inches and 0.118 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.190 inches
Grip Length:
Between 1.552 inches and 1.572 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams 5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjc
Specification Data:
80205-nas1123 professional/industrial association standard
Shelf Life:

N/a

NSN 5305-01-438-2250

Close Tolerance Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0