NSN 5305-01-438-2253

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-438-2253 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.276 inches **Fastener Length:** Between 1.386 inches and 1.416 inches **Head Style:** Flat fillister **Head Diameter:** Between 0.265 inches and 0.270 inches **Head Height:** Between 0.088 inches and 0.102 inches **Grip Diameter:** Between 0.1625 inches and 0.1635 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.164 inches **Grip Length:** Between 1.115 inches and 1.135 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches threads **Product Name:** Navy special project Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response

Thread Series Designator: Unjc

Specification Data:

80205-nas1122 professional/industrial association standard

NSN 5305-01-438-2253

Close Tolerance Screw - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0