NSN 5305-01-438-2267

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-438-2267

3aThread Direction:Right-handThread Length:0.276 inchesFastener Length:Between 0.511 inches and 0.541 inchesHead Style:Flat fillisterHead Diameter:Between 0.265 inches and 0.270 inchesHead Height:Between 0.088 inches and 0.102 inchesGrip Diameter:Between 0.1625 inches and 0.1635 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.164 inchesGrip Length:10164 inchesGrip Length:117000 pounds per square inchSurface Finish:32.0 microinches threadsMaterial:10.100 pounds per square inchSurface Finish:32.0 microinches threadsMaterial:11700 Pounds per square inchSurface Finish:32.0 microinches threadsMaterial:12.1 microinches threadsMaterial:12.2 microinches threadsMaterial:12.3 microinches threadsMaterial:13.4 microinches threadsMaterial:14.5 microinches threadsMaterial:15.7 microinches threadsMaterial:17.7 microinches threadsMaterial:17.7 microinches threadsMaterial:17.7 microinches threadsMaterial:17.7 microinches threadsMaterial:17.7 microinches threads17.7 microinches threads17.7 microinch	Thread Class:
Right-handRight-handThread Length:0.276 inchesFastener Length:Between 0.511 inches and 0.541 inchesHead Style:Flat fillisterHead Diameter:Between 0.265 inches and 0.270 inchesHead Height:Between 0.088 inches and 0.102 inchesGrip Diameter:Between 0.1625 inches and 0.102 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.164 inchesGrip Length:Between 0.240 inches and 0.260 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchSurface Finish:32.0 microinches threadsMaterial:Iron alloy 660Material Specification:Arns 5737 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:	3a
Tread Length:0.276 inchesFastener Length:Between 0.511 inches and 0.541 inchesHead Style:Flat fillisterHead Diameter:Between 0.265 inches and 0.270 inchesHead Height:Between 0.088 inches and 0.102 inchesGrip Diameter:Between 0.1625 inches and 0.102 inchesGrip Diameter:Between 0.1625 inches and 0.1635 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.164 inchesGrip Length:Between 0.240 inches and 0.260 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchSurface Finish:32.0 microinches threadsMaterial:Iron alloy 660Material Specification:Arns 5737 asen standard single material responseSurface Treatment:PassivateSurface Treatment:Passivate	Thread Direction:
0.276 inches Fastener Length: Between 0.511 inches and 0.541 inches Head Style: Flat fillister Head Diameter: Between 0.265 inches and 0.270 inches Head Height: Between 0.265 inches and 0.270 inches Grip Diameter: Between 0.088 inches and 0.102 inches Grip Diameter: Between 0.1625 inches and 0.102 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.164 inches Grip Length: Between 0.240 inches and 0.260 inches Internal Q ty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5737 asen standard single material response Surface Treatment: Passivate	Right-hand
Fastener Length:Fastener Length:Between 0.511 inches and 0.541 inchesHead Style:Flat fillisterHead Diameter:Between 0.265 inches and 0.270 inchesHead Height:Between 0.088 inches and 0.102 inchesGrip Diameter:Between 0.1625 inches and 0.102 inchesGrip Diameter:Between 0.1625 inches and 0.1635 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.164 inchesGrip Length:Between 0.240 inches and 0.260 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchSurface Finish:32.0 microinches threadsMaterial:Iron alloy 660Material Specification:Arms 5737 assn standard single material responseSurface Treatment:PassivateSurface Treatment:Passivate	Thread Length:
Between 0.511 inches and 0.541 inchesHead Style:Flat fillisterHead Diameter:Between 0.265 inches and 0.270 inchesHead Height:Between 0.088 inches and 0.102 inchesGrip Diameter:Between 0.1625 inches and 0.1635 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.164 inchesGrip Length:Between 0.240 inches and 0.260 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchSurface Finish:32.0 microinches threadsMaterial:Iron alloy 660Material Specification:Arns 5737 assn standard single material responseSurface Treatment:PassivateSurface Treatment:PassivateSurface Treatment Specification:	0.276 inches
Head Style:Flat fillisterHead Diameter:Between 0.265 inches and 0.270 inchesHead Height:Between 0.088 inches and 0.102 inchesGrip Diameter:Between 0.1625 inches and 0.1635 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.164 inchesGrip Length:Between 0.240 inches and 0.260 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchSurface Finish:32.0 microinches threadsMaterial:Iron alloy 660Material Specification:Arns 5737 assn standard single material responseSurface Treatment:PassivateSurface Treatment:PassivateSurface Treatment Specification:	Fastener Length:
Flat fillisterHead Diameter:Between 0.265 inches and 0.270 inchesHead Height:Between 0.088 inches and 0.102 inchesGrip Diameter:Between 0.1625 inches and 0.1635 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.164 inchesGrip Length:Between 0.240 inches and 0.260 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchSurface Finish:32.0 microinches threadsMaterial:Iron alloy 660Material Specification:Arns 5737 assn standard single material responseSurface Treatment:PassivateSurface Treatment:Passivate	Between 0.511 inches and 0.541 inches
Head Diameter:Between 0.265 inches and 0.270 inchesHead Height:Between 0.088 inches and 0.102 inchesGrip Diameter:Between 0.1625 inches and 0.1635 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.164 inchesGrip Length:Between 0.240 inches and 0.260 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchSurface Finish:32.0 microinches threadsMaterial:Iron alloy 660Material Specification:Ams 5737 assn standard single material responseSurface Treatment:PassivateSurface Treatment:PassivateBurface Treatment:PassivateSurface Treatment Specification:	Head Style:
Between 0.265 inches and 0.270 inchesHead Height:Between 0.088 inches and 0.102 inchesGrip Diameter:Between 0.1625 inches and 0.1635 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.164 inchesGrip Length:Between 0.240 inches and 0.260 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchSurface Finish:32.0 microinches threadsMaterial:Iron alloy 660Material Specification:Ams 5737 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:	Flat fillister
Head Height:Between 0.088 inches and 0.102 inchesGrip Diameter:Between 0.1625 inches and 0.1635 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.164 inchesGrip Length:Between 0.240 inches and 0.260 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchSurface Finish:32.0 microinches threadsMaterial:Iron alloy 660Material Specification:Ams 5737 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:	Head Diameter:
Between 0.088 inches and 0.102 inchesGrip Diameter:Between 0.1625 inches and 0.1635 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.164 inchesGrip Length:Between 0.240 inches and 0.260 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchSurface Finish:32.0 microinches threadsMaterial:Iron alloy 660Material Specification:Ams 5737 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:	Between 0.265 inches and 0.270 inches
Grip Diameter:Between 0.1625 inches and 0.1635 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.164 inchesGrip Length:Between 0.240 inches and 0.260 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchSurface Finish:32.0 microinches threadsMaterial:Iron alloy 660Material Specification:Ams 5737 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:	Head Height:
Between 0.1625 inches and 0.1635 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.164 inchesGrip Length:Between 0.240 inches and 0.260 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchSurface Finish:32.0 microinches threadsMaterial:Iron alloy 660Material Specification:Ams 5737 assn standard single material responseSurface Treatment:PassivateSurface Treatment:	Between 0.088 inches and 0.102 inches
Internal Drive Style:Offset cruciform (torque set)Thread Diameter:0.164 inchesGrip Length:Between 0.240 inches and 0.260 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchSurface Finish:32.0 microinches threadsMaterial:Iron alloy 660Material Specification:Ams 5737 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:	Grip Diameter:
Offset cruciform (torque set) <b>Thread Diameter:</b> 0.164 inches <b>Grip Length:</b> Between 0.240 inches and 0.260 inches <b>Thready Qty Per Inch (tpi):</b> 32 <b>Min. Tensile Strength (psi):</b> 160000 pounds per square inch <b>Surface Finish:</b> 32.0 microinches threads <b>Material:</b> Iron alloy 660 <b>Material Specification:</b> Ams 5737 assn standard single material response <b>Surface Treatment:</b> Passivate <b>Surface Treatment:</b>	Between 0.1625 inches and 0.1635 inches
Thread Diameter:0.164 inchesGrip Length:Between 0.240 inches and 0.260 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchSurface Finish:32.0 microinches threadsMaterial:Iron alloy 660Material Specification:Ams 5737 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:	Internal Drive Style:
0.164 inches Grip Length: Between 0.240 inches and 0.260 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:	Offset cruciform (torque set)
Grip Length: Between 0.240 inches and 0.260 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:	Thread Diameter:
<ul> <li>Between 0.240 inches and 0.260 inches</li> <li>Thready Qty Per Inch (tpi):</li> <li>32</li> <li>Min. Tensile Strength (psi):</li> <li>160000 pounds per square inch</li> <li>Surface Finish:</li> <li>32.0 microinches threads</li> <li>Material:</li> <li>Iron alloy 660</li> <li>Material Specification:</li> <li>Ams 5737 assn standard single material response</li> <li>Surface Treatment:</li> <li>Passivate</li> <li>Surface Treatment Specification:</li> </ul>	0.164 inches
Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:	Grip Length:
32 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Arns 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:	Between 0.240 inches and 0.260 inches
<ul> <li>Min. Tensile Strength (psi):</li> <li>160000 pounds per square inch</li> <li>Surface Finish:</li> <li>32.0 microinches threads</li> <li>Material:</li> <li>Iron alloy 660</li> <li>Material Specification:</li> <li>Ams 5737 assn standard single material response</li> <li>Surface Treatment:</li> <li>Passivate</li> <li>Surface Treatment Specification:</li> </ul>	Thready Qty Per Inch (tpi):
160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:	32
Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:	Min. Tensile Strength (psi):
32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:	160000 pounds per square inch
Material:Iron alloy 660Material Specification:Ams 5737 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:	Surface Finish:
Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:	32.0 microinches threads
Material Specification:Ams 5737 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:	Material:
Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:	Iron alloy 660
Surface Treatment: Passivate Surface Treatment Specification:	Material Specification:
Passivate Surface Treatment Specification:	Ams 5737 assn standard single material response
Surface Treatment Specification:	Surface Treatment:
-	Passivate
Qq-p-35 federal specification single treatment response	Surface Treatment Specification:
	Qq-p-35 federal specification single treatment response
Thread Series Designator:	Thread Series Designator:
Unjc	Unjc
Specification Data:	Specification Data:
80205-nas1122 professional/industrial association standard	80205-nas1122 professional/industrial association standard
Shelf Life:	Shelf Life:
N/a	N/a

## NSN 5305-01-438-2267

Close Tolerance Screw - Page 2 of 2

AeroBase Group

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0