NSN 5305-01-438-3775

Between 0.400 inches and 0.450 inches

Between 0.660 inches and 0.690 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

Fastener Length:

За

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-438-3775

Head Style:						
Flat countersunk						
Head Diameter:						
Between 0.449 inches and 0.507 inches						
Locking Feature:						
Patch threads or pellet threads or strip threads						
Grip Diameter:						
Between 0.2485 inches and 0.2495 inches						
Internal Drive Style:						
Offset cruciform (torque set)						
Thread Diameter:						
0.250 inches						
Grip Length:						
Between 0.240 inches and 0.250 inches						
Thready Qty Per Inch (tpi):						
28						
Min. Tensile Strength (psi):						
160000 pounds per square inch						
Hardness Rating:						
36.0 rockwell c and 40.0 rockwell c						
Countersink Angle:						
Between 99.0 degrees and 101.0 degrees						
Surface Finish:						
32.0 microinches threads						
Product Name:						
Navy special project						
Material:						
Steel comp 4140 or steel comp 8740						
Surface Treatment:						
Cadmium						
Surface Treatment Specification:						
Qq-p-416 tii c2 assn standard single treatment response						
Thread Series Designator:						
Unjf						

NSN 5305-01-438-3775

Close Tolerance Screw - Page 2 of 2



		fe	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0