NSN 5305-01-438-5204

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-438-5204

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.316 inches
Fastener Length:
Between 0.739 inches and 0.769 inches
Head Style:
Flat fillister
Head Diameter:
Between 0.365 inches and 0.375 inches
Head Height:
Between 0.133 inches and 0.150 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.250 inches
Grip Length:
Between 0.428 inches and 0.448 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches threads
Product Name:
Navy special project
Material:
Iron alloy 660
Material Specification:
Ams 5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1124 professional/industrial association standard

NSN 5305-01-438-5204

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

