## NSN 5305-01-438-5208

View Online at https://aerobasegroup.com/nsn/5305-01-438-5208

Machine Screw - Page 1 of 2

**Thread Class:** 

32.0 microinches

32.0 microinches

**Thread Surface Finish:** 



За **Thread Direction:** Right-hand Thread Length: 0.200 inches **Fastener Length:** Between 0.229 inches and 0.250 inches **Head Style:** Fillister **Head Diameter:** Between 0.178 inches and 0.183 inches **Head Height:** Between 0.059 inches and 0.069 inches **Locking Feature:** Strip **Internal Drive Style:** Torque set **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Iron alloy 660 **Locking Feature Material:** Plastic polychlorotrifluoroethylene **Screw Material Specification:** Ams 5737 assn standard single material response **Locking Feature Material Specification:** Ams 3650 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Bearing Surface Of Head Surface Finish:** 32.0 microinches **Shank Surface Finish:** 

## NSN 5305-01-438-5208

Machine Screw - Page 2 of 2

A500d0



Thread Series Designator:
Unjc
Specification Data:
80205-nas1191 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: