

View Online at <https://aerobasegroup.com/nsn/5305-01-438-5208>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.200 inches

Fastener Length:

Between 0.229 inches and 0.250 inches

Head Style:

Fillister

Head Diameter:

Between 0.178 inches and 0.183 inches

Head Height:

Between 0.059 inches and 0.069 inches

Locking Feature:

Strip

Internal Drive Style:

Torque set

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

160000 pounds per square inch

Screw Material:

Iron alloy 660

Locking Feature Material:

Plastic polychlorotrifluoroethylene

Screw Material Specification:

Ams 5737 assn standard single material response

Locking Feature Material Specification:

Ams 3650 assn standard single material response

Screw Surface Treatment:

Passivate

Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Bearing Surface Of Head Surface Finish:

32.0 microinches

Shank Surface Finish:

32.0 microinches

Thread Surface Finish:

32.0 microinches

Thread Series Designator:

Unjc

Specification Data:

80205-nas1191 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0