NSN 5305-01-438-6316

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-438-6316 **Thread Direction:** Right-hand **Thread Length:** Between 4.75 millimeters and 5.25 millimeters Fastener Length: Between 21.75 millimeters and 22.25 millimeters **Head Style:** Pan no. 2 **Head Diameter:** Between 6.75 millimeters and 7.25 millimeters **Head Height:** Between 3.25 millimeters and 3.75 millimeters **Locking Feature:** Patch threads **First Diameter From Head:** Between 2.94 millimeters and 3.06 millimeters Distance From Largest Bearing Surface Of Head To End Of First Diameter: 17.0 millimeters **Internal Drive Style:** Cross recess type ii **Thread Diameter:** 4.0 millimeters Min. Tensile Strength (psi): 80000 pounds per square inch **Thread Pitch In Millimeters:** 0.7 **External Thread Tolerance Class: Externally Relieved Body Diameter Quantity: Special Features:** Self-lockingpatch nylon I-p-410 Color: Black Material: Steel comp 301 **Material Specification:** Qq-s-763 military specification single material response and fed-std66 military specification single material response **Surface Treatment:** Oxide

Surface Treatment Specification:

Mil-c-13924 military specification single treatment response

NSN 5305-01-438-6316

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
M
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

spec.