## NSN 5305-01-438-8787



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-438-8787 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.667 inches **Fastener Length:** Between 0.719 inches and 0.750 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.021 inches and 0.034 inches **Head Height:** 0.083 inches **Internal Drive Style:** Cross recess type iii **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Screw Surface Treatment:** Oxide **Screw Surface Treatment Specification:** Mil-c-13924 military specification single treatment response Color: Black **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A500d0

## NSN 5305-01-438-8787

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-13924 spec.