NSN 5305-01-439-0141

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-439-0141 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.360 inches and 0.390 inches **Fastener Length:** Between 1.173 inches and 1.203 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.750 inches and 0.765 inches **Head Height:** Between 0.240 inches and 0.260 inches **First Diameter From Head:** Between 0.230 inches and 0.240 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.802 inches and 0.822 inches **Point Style:** Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.3125 inches Thready Qty Per Inch (tpi): 18 **Externally Relieved Body Diameter Quantity:** Material: Stainless steel **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-439-0141

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0