## NSN 5305-01-439-4216

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-439-4216

| Thread Direction:   |
|---|
| Right-hand  |
| Thread Length:  |
| Between 4.5 millimeters and 5.0 millimeters   |
| Fastener Length:  |
| Between 4.5 millimeters and 5.0 millimeters   |
| Head Style:   |
| Pan   |
| Head Diameter:  |
| Between 3.94 millimeters and 4.24 millimeters   |
| Head Height:  |
| Between 1.40 millimeters and 1.60 millimeters   |
| Locking Feature:  |
| Patch   |
| Internal Drive Style:   |
| Cross recess type ii  |
| Thread Diameter:  |
| 2.2 millimeters   |
| Thread Pitch In Millimeters:  |
| 0.45  |
| External Thread Tolerance Class:  |
| 6g  |
| Screw Material:   |
| Stainless steel   |
| Locking Feature Material:   |
| Plastic polyamide   |
| Screw Material Specification:   |
| Qq-s-763 federal specification single material response or 66 federal standard single material response |
| Locking Feature Material Specification:   |
| L-p-410 federal specification single material response  |
| Screw Surface Treatment:  |
| Passivate   |
| Screw Surface Treatment Specification:  |
| Qq-p-35 federal specification single treatment response   |
| Thread Series Designator:   |
| M   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |
| NI.   |

No

## **NSN 5305-01-439-4216**Machine Screw - Page 2 of 2



Fiig:

A500d0