NSN 5305-01-439-6845

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-439-6845 **Thread Direction:** Right-hand Thread Length: Between 4.75 millimeters and 5.25 millimeters Fastener Length: Between 20.75 millimeters and 21.25 millimeters **Head Style:** Pan no. 2 **Head Diameter:** Between 6.75 millimeters and 7.25 millimeters **Head Height:** Between 3.25 millimeters and 3.75 millimeters **Locking Feature:** Patch threads **First Diameter From Head:** Between 2.94 millimeters and 3.06 millimeters Distance From Largest Bearing Surface Of Head To End Of First Diameter: 16.0 millimeters **Internal Drive Style:** Cross recess type ii **Thread Diameter:** 4.0 millimeters **Thread Pitch In Millimeters:** 0.7 **External Thread Tolerance Class: Externally Relieved Body Diameter Quantity: Special Features:** Nylon locking element 6/6 i/a/w I-p-410 to threads Material: Steel **Material Specification:** Qq-s-763 cres 300 series military specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 type 2 military specification single treatment response **Thread Series Designator:** Μ

Shelf Life:

N/a

NSN 5305-01-439-6845

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:	
No	
Fiig:	
A003b0	

Mil-std (military Standard):

Unit Of Measure:

spec.